

TECHNICAL DATASHEET

CYLINDER PRESSURE TEST GAUGE



DESCRIPTION

The cylinder pressure test gauge consists of a nickel-plated brass body that incorporates a bleed valve, operated by rotating a finger screw. The gauge mounted into the top of this body is a 350 bar gauge with a luminous face. The handwheel and liner enables the test gauge to be screwed into both 200 and 300 bar cylinder valves with an EN144-2 thread and allows the cylinder contents to be checked quickly and easily with minimum loss of pressure.

APPLICATIONS

The cylinder pressure test gauge is specifically designed for checking the contents of a cylinder whilst it is not connected to a BA set.

PART NUMBER

1023116/035.016.03	Test Gauge
--------------------	------------

MATERIALS

Body	Nickel Plated Brass
Handwheel	Glass filled Polyamide
Cylinder connector liner	Stainless steel
O-Rings	Nitrile, Silicone, EPDM
Crush seal	Copper
HP Pressure Gauge	Stainless Steel, Polycarbonate Lens
HP Pressure Gauge Cover	Neoprene

TECHNICAL SPECIFICATIONS

Pressure Indicator

Bourdon tube type dial indicator	
Heat and impact resistant Polycarbonate lens	
Safety blow-out vent in rear of gauge	
Accuracy	+/- 10 bar between 40-300 bar