



CSR2-CE PULLEYS

PART NUMBERS:

300343-CE - CSR2-CE Pulley

300342-CE - CSR2-CE Double Pulley



InterFire
AGENCIES

Pat. 7,419,138

The design of our redesigned CSR2 (Confined Space Rescue) Pulley is stronger yet lighter and incorporates 7/16 in (11 mm) to 1/2 in (13 mm) life safety rope. Ideal for industrial applications as well as many rescue operations, the CSR2 uses our proprietary, patented locking system, which eliminates a toothed cam or Prusik so it can be easily and safely released while under load. (The absence of the toothed cam means that even if the system is fully collapsed and pulled tight, it can still be released easily. Systems using a toothed cam must be raised even further before the cam can be released, which can be impossible if the system is fully collapsed without thinking about this problem ahead of time – causing potential problems with the load on the system becoming stuck.) An integral thrust-bearing swivel reduces torque by aligning the pulley with the load, thereby increasing efficiency and safety. Its larger size allows for the easy application of rescue-size carabiners.

Machined from a solid block of aircraft-grade aluminum, the CSR2 features a high-strength aluminum side plate, sealed bearings and anodized aluminum sheaves. The side bucket location allows for maximum lift height and full retraction of the system, and a removable bucket cover facilitates changing out lifeline with sewn terminations.

All-new stronger, lighter-weight design

Compatible with 11-13 mm life safety rope

Meets NFPA 1983 (2017 ED) – General Use

CSR2 Pulley MBS 46 kN (10,341 lbf) / CSR2 Double Pulley MBS 45 kN (10,116 lbf)

Machined from solid block of aircraft-grade aluminum

Made in USA



300343-CE CSR2-CE Pulley



300342-CE CSR2-CE Double Pulley



AVAILABLE FROM



Unit 1 / 23 Christable Way
LANDSDALE WA 6055
+ 61 8 6201 3170
interfireagencies.com.au
info@interfireagencies.com.au