

Banshee[™] Siren Amplifier System

The only siren amplifier system on the market today with the ability to upgrade your siren into a dual tone siren delivering twice the warning sound at intersections and high risk areas!

A PUBLIC SAFETY EQUIPMENT COMPANY

BansheeTM Siren Apublic safety equipment www.code3pse.com Amplifier System



The New Sound in Emergency Response

Benefits

- ▶ The only complete siren amplifier system with dual tone capability, low frequency, electronic air horn, plus additional built in specialty tones all in one box — that provides phenomenal audio impact.
- ▶ Unique tones or tone combinations (3) low frequency tones and special tones such as Command Alert and Airhorn, can be activated while your primary siren tone is running to really grab driver's attention.
- ► Works with one set of standard size speakers no need to install special large speakers saving you time on installation and space inside of your vehicle.

Features

- Eight Universal Dual Tones (Wail, Yelp, Hyper-Yelp 1, Hyper-Yelp 2, Hi-Lo 1, Hi-Lo 2, Hyper-Lo 1, Hyper-Lo 2).
- Three Low Frequency Tones (Synchronized 1/2) Frequency, Low Frequency Yelp and Low Frequency Wail).
- Eight Low Frequency Time Out settings (7.5, 15, 22.5, 30, 37.5, 45, 52.5 and 60 seconds).
- Operate the electronic Airhorn independently of the primary siren (by itself as an alert) or while the primary siren is in full operation.
- Unique CommandAlert and Yelp Stop tones.
- Additional tones are available when the Banshee operates with a Code 3 Z3 siren.
- Universal Dual Tone operation with most industry standard sirens.

- All inputs can be configured for positive or negative activation.
- Comes with Banshee amplifier box, the power control harness bag, and a CAT5 cable

Specifications

- Box dimensions: 8 ½" L x 2.8" H x 5.7" W
- 10-16 VDC
- 100W: 8 Amps @ 13.6V with 11-ohm load (100 Watt Speaker)
- 200W: 14 Amps @ 13.6V with 5.5-ohm load (2-100 Watt Speakers)
- Box weight: 3.2 pounds
- SAE J1849, CA Title 13 when properly configured

