

INTRINSICALLY SAFE DUAL-LIGHT ANGLE LIGHT

NIGHTSTICK®
Life Depends on Light™

INTRANTDUO



HI VIS GREEN XPP-5564GXA



ORANGE XPP-5564RXA



Battery status indicator - green indicates full charge and glows red when battery is nearing low



275 lumen floodlight - wide illumination at precise **45° downward angle**



Easy press switches, independently controlling **separate LEDs**



Spring loaded clip and V-ring **securely hold tight to gear** in any situation



320 LUMENS

INTRANTDUO

DUAL-LIGHT ANGLE LIGHT

4AA**ITEM NUMBER/UPC**

XPP-5564RXA (Red), 017398809245
XPP-5564GXA (Green), 017398809238

MARKET APPLICATIONS

Hazardous work environments, fire, rescue, industrial and automotive

CERTIFICATIONS

- CE, cETLus, ATEX, IECEx, NFPA

CASE MATERIAL

- PC/ABS

LUMENS/RUNTIME**FLASHLIGHT**

- HIGH: 320L, 8 hrs. runtime
- LOW: 100L, 15 hrs. runtime

FLOODLIGHT

- HIGH: 275L, 8 hrs. runtime
- LOW: 100L, 28 hrs. runtime

DUAL-LIGHT

- 320L, 5 hrs. runtime

CANDELA**FLASHLIGHT**

- HIGH: 22,107
- LOW: 7,333

BEAM DISTANCE**FLASHLIGHT**

- HIGH: 297m
- LOW: 171m

WATER RATING

- IP-67 (Dustproof and Waterproof)

DROP RATING

- 2 meters

DIMENSIONS

- LENGTH: 6.25 in (159 mm)
- WIDTH: 2.75 in (70 mm)
- DEPTH: 2.5 in (64 mm)
- HEAD DIAMETER: 2.75 in (70 mm)
- WEIGHT: 11 oz (312g with batteries)

BATTERY

- 4AA batteries (included)

WARRANTY

- Limited Lifetime Warranty

WHAT'S INCLUDED

- Angle light
- Instruction manual

FL1 STANDARD	SPOT HIGH	SPOT LOW	DUAL-LIGHT
	320 LUMENS	100 LUMENS	320 LUMENS
	8h	15h	5h
	300m		
	22107cd		

Bayco Products, Inc. XPP-5564GXA/RXA
640 S. Sanden Blvd., Wylie, TX 75098



Ex ia FLASHLIGHT FOR USE IN HAZARDOUS LOCATIONS
For use with Bayco 5564-CARRIER with 4 AA Energizer Type
EN91, E91, Panasonic LR6XWA or Duracell MN1500 batteries only

Intertek

ID 5012927

ELECTRICAL SAFETY
INTRINSICALLY SAFE
SECURITE INTRINSEQUE

CLASS I DIV 1 GRPS A-D T4
CLASS II & III DIV 1 GRPS E-G T135°C
CLASS I ZONE 0 AEx ia IIC T4 Ga
ZONE 20 AEx ia IIC T135°C Da
I M1 Ex ia I Ma
II 1 G Ex ia IIC T4 Ga
II 1 D Ex ia IIC T135°C Da

Ex ia I Ma
Ex ia IIC T4 Ga
Ex ia IIC T135°C Da
IECEx: IECEx ETL 23.0048X
ATEX: ITS I24ATEX39286X
-20°C ≤ Tamb ≤ +40°C
1.5V/Cell Alkaline

CE 2575



CERTIFIED



AVAILABLE FROM



National Sales Office & Warehouse
Unit 1 / 23 Christable Way
LANDSDALE Western Australia 6055
1300 922 303
+ 61 8 6201 3170
interfire.com.au
info@interfire.com.au

South Australian Office &
Warehouse Unit 9 / 28 Heath St
LONSDALE South Australia, 5160
1300 922 303
+ 61 8 6201 3170
interfire.com.au
info@interfire.com.au