



HANDLINE NOZZLES

HEAVY-DUTY PROFESSIONAL AND INDUSTRIAL FIRE FIGHTING NOZZLES



VIPER® SELECT

- Constant gallonage in all positions and flows.
- 4 Gallonage selection ring, without pattern changes.
- Flush position capable of flushing without pattern changes or shutting down.
- Extruded E-LITE alloy, lightweight, hard-coated and durable.
- Durable polymer shut-off handles.
- Designed for use with foam eductors and CEP foam tubes.
- Spinning Teeth in polyamide with fiber, Zamak and also Stainless Steel (under request).

HANDLINE NOZZLES



ERGONOMIC
HANDLE

HARD ANODIZED
EXTRUDED
ALUMINIUM

SWIVEL INLET

ALUMINIUM PISTOL GRIP
COVERED WITH
THERMO RUBBER

MULTIPLE
FLOW SETTINGS

PROTECTIVE
RUBBER BUMPER

SPINNING
TEETH

FLUSH WITHOUT CHANGING PATTERN
OR SHUTTING DOWN

HIGH VISIBILITY AND DURABILITY
OPERATING LABELS

HIGH PERFORMANCE NOZZLES WITH MULTIPLE CONSTANT GALLONAGE FLOWS.

VIPER® SELECT



www.interfireagencies.com.au

info@interfireagencies.com.au

DATA MEASUREMENTS AT 7 BAR (100 PSI PRESSURE)
(5 & 6 BAR AVAILABLE)

VIPER® SELECT



1"VIPER SELECT

NOZZLE	POSITION	NOZZLE FLOW		EFFECTIVE REACH		MODEL	SWIVEL INLET	WEIGHT		LENGTH	
		GPM	LPM	Feet	Meters		Inches	Lbs	Kg	Inches	cm
SG 540	1	5	19	50	15	SG 540	1"	2.75	1.25	7.87	20
	2	10	37	60	18						
	3	24	90	80	24						
	4	40	150	92	28						
SG 1560	1	15	50	62	19	SG 1560	1"	3.44	1.56	7.87	20
	2	30	125	85	26	SG1560 TIP	1-1/2"	1.94	0.88	5.9	15
	3	50	200	98	30						
	4	60	230	112	34						



1 1/2"VIPER SELECT

NOZZLE	POSITION	NOZZLE FLOW		EFFECTIVE REACH		MODEL	SWIVEL INLET	WEIGHT		LENGTH	
		GPM	LPM	Feet	Meters		Inches	Lbs	Kg	Inches	cm
SG 3012	1	30	115	85	26	SG 3012	1-1/2"	4.3	1.95	8.85	22
	2	60	230	112	34	SG 3012 TIP	1-1/2"	2.8	1.27	6.1	15
	3	95	360	131	40						
	4	125	475	141	43						
SG 7515	1	75	265	118	36	SG 7515	1-1/2"	4.3	1.95	8.85	22
	2	100	380	138	42	SG 7515 TIP	1-1/2"	2.8	1.27	6.1	15
	3	125	500	144	44						
	4	150	600	148	45						



2 1/2"VIPER SELECT

NOZZLE	POSITION	NOZZLE FLOW		EFFECTIVE REACH		MODEL	SWIVEL INLET	WEIGHT		LENGTH	
		GPM	LPM	Feet	Meters		Inches	Lbs	Kg	Inches	cm
SG 9520	1	95	350	128	39	SG 9520	1-1/2"	6.57	2.98	11.2	28
	2	125	500	141	43	SG 9520	2-1/2"	7.3	3.31	12.8	33
	3	150	600	148	45	SG 9520 TIP	1-1/2"	3.8	1.72	8.6	22
	4	200	800	154	47						
SG 12250	1	125	500	131	40	SG 12250	2-1/2"	7.3	3.31	12.8	33
	2	150	600	144	44	SG 12250 TIP	1-1/2"	3.8	1.72	8.6	22
	3	200	800	151	46						
	4	250	1000	157	48						

HANDLINE NOZZLES

VIPER® SELECT