

DATASHEET

PILLAR STEEL SG



GENERAL

Art.Nr:	H-287-SG	Standards:	EN 12275-B:2013,EN 362-M:2004
GTIN:	8056734830712	Net weight:	0.18 kg
E-class number:	40-21-07-12	Gross weight:	0.18 kg
Customs tariff number:	73269098		

DATASHEET

PILLAR STEEL SG

Zinc-plated steel carabiner with screwgate, designed for lowering, working at height, industrial safety and rescue.

Main features:

- great strength and durability, high work loads;
- ideal for lowering, working at height, hauling and rescue maneuvers;
- zinc-plated finish prevents rust formation in moist environments;
- catch-free nose avoids snagging when clipping and unclipping.

FEATURES

Application areas:

Various, Arborists, Elevator construction, Emergency, Facades cleaning, Work on roofs and facades, High Rack storage, High ropes courses, Tactical approach, Mobile platforms, Mobile Work Platforms, Off Shore Industry, Rope access, Rescue, Roofers, Route construction, Scaffolding, Shaft, Steelwork, Working on masts and towers, Wind energy, Working in confined spaces

Colour:	Silver
Swivel:	No
Carabiner properties:	Corrosion resistance
Fallindicator:	No
Gate opening:	20 mm
MBS MAJOR AXIS:	30 kN
MBS GATE OPEN:	10 kN
MBS MINOR AXIS:	15 kN
Form fit:	Key Lock
Carabiner type:	Type B (EN 12275: 2013), Type M (EN 362:2004)
Maximum lifetime:	30 years
Minimum temperature:	-35 °C
Maximum temperature:	45 °C

DATASHEET

PILLAR STEEL SG

Standard ANSI:	No
UIAA compliance:	No
Anti-twist device:	No
Carabiner clasp:	Screwlock

MATERIAL

Material:	Steel
-----------	-------