

## DATASHEET

### SNAPPY STEEL SG



#### GENERAL

|                        |               |               |                                          |
|------------------------|---------------|---------------|------------------------------------------|
| Art.Nr:                | H-291-SG      | Standards:    | EN 12275-H:2013, EN 362-B:2004, UIAA 121 |
| GTIN:                  | 8056734831702 | Net weight:   | 0.24 kg                                  |
| E-class number:        | 40-21-07-12   | Gross weight: | 0.24 kg                                  |
| Customs tariff number: | 73269098      |               |                                          |

# DATASHEET

## SNAPPY STEEL SG

Zinc plated steel connector with screw gate, ideal for working at height, hauling and rescue manoeuvres.

### Main characteristics:

- great strength and durability, high work loads;
- zinc-plated finish prevents rust formation in moist environments;
- catch-free nose avoids snagging when clipping and unclipping.

### FEATURES

#### Application areas:

Various, Arborists, Elevator construction, Emergency, Facades cleaning, Work on roofs and facades, High Rack storage, High ropes courses, Tactical approach, Mobile platforms, Mobile Work Platforms, Off Shore Industry, Rope access, Rescue, Roofers, Route construction, Scaffolding, Shaft, Steelwork, Working on masts and towers, Wind energy, Working in confined spaces

|                       |                                               |
|-----------------------|-----------------------------------------------|
| Colour:               | Silver                                        |
| Swivel:               | No                                            |
| Carabiner properties: | Corrosion resistance                          |
| Fallindicator:        | No                                            |
| Gate opening:         | 22 mm                                         |
| MBS MAJOR AXIS:       | 40 kN                                         |
| MBS GATE OPEN:        | 15 kN                                         |
| MBS MINOR AXIS:       | 15 kN                                         |
| Form fit:             | Key Lock                                      |
| Carabiner type:       | Type H (EN 12275: 2013), Type M (EN 362:2004) |
| Maximum lifetime:     | 30 years                                      |
| Minimum temperature:  | -35 °C                                        |
| Maximum temperature:  | 45 °C                                         |

# DATASHEET

## SNAPPY STEEL SG

|                    |           |
|--------------------|-----------|
| Standard ANSI:     | No        |
| Standard CSA:      | No        |
| UIAA compliance:   | Yes       |
| Anti-twist device: | No        |
| Carabiner clasp:   | Screwlock |

### **MATERIAL**

|           |       |
|-----------|-------|
| Material: | Steel |
|-----------|-------|