

DATASHEET

Q-LINK 08



GENERAL

Art.Nr:	H-320-08	Standards:	EN 12275:2013/Q,EN 362:2004/Q,UIAA 121
GTIN:	3351770010704	Net weight:	0.08 kg
E-class number:	40-21-07-12	Gross weight:	0.08 kg
Customs tariff number:	76169990		

DATASHEET

Q-LINK 08

Galvanized-steel quick link, oval shaped Ø 8 mm, extremely sturdy and designed to withstand high loads on all axes. Ideal to be used as a lowering anchorage, for fixed quickdraws, work at height, industrial safety and rescue.

When closed with a wrench, it becomes a semi-permanent anchor.

FEATURES

Application areas:	Various
Colour:	Silver
Swivel:	No
Carabiner properties:	Corrosion resistance
Fallindicator:	No
Gate opening:	11 mm
MBS MAJOR AXIS:	35 kN
MBS MINOR AXIS:	10 kN
Form fit:	Hook-Nose
Carabiner type:	Type Q (EN 12275: 2013), Type Q (EN 362:2004)
Maximum lifetime:	30 years
Minimum temperature:	-35 °C
Maximum temperature:	45 °C
Standard ANSI:	No
Standard CSA:	No
UIAA compliance:	Yes
Anti-twist device:	No
Carabiner clasp:	Screwlock

MATERIAL

Material:	Steel
-----------	-------

DATASHEET

Q-LINK 08

