

FIRELITE

Application

FIRE HOSE

Paroilys
Standard norms: NF S61112, BS 6391 Type 3
Australian Standards Class H Fire Hose AS2792

Features

- An economic price hose constructed with a woven textile reinforcement encased in an elastomer rubber which forms a unified lining and cover. High quality rubber covered hose. A superior alternative to traditional conventional textile jacket fire hose manufactured by coating process
- 5 years of warranty from defects in materials and workmanship
- Highly flexible and ligthweight for ease of handling
- Maintenance free
- Easy to repair

Technical data:

Diameter		Weight	Working pressure		Bursting pressure	
mm	inch	g/m	bar	PSI	bar	PSI
25	1	170	20	300	65	975
38	1 1/2	250	17	255	50	750
45	1 3/4	290	17	255	50	750
64	2 1/2	450	17	255	50	750
70	2 3/4	500	17	255	50	750
110		950	13	195	40	600

Right is reserved to modify any specification without prior notice
Other diameter on request

Construction

- **WOVEN TEXTILE JACKET:** all synthetic yarns
- **LINING**: synthetic elastomer rubber
- **OUTSIDE COVER**: synthetic elastomer rubber smooth cover
- **COLOR**: red

AVAILABLE FROM

InterFire AGENCIES

National Sales Office & Warehouse
Unit 1 / 23 Christable Way
LANDSDALE Western Australia 6055

South Australian Office & Warehouse
Unit 2 / 347 Main South road
MORPHETT VALE South Australia 5162

New South Wales Office
PO BOX 407
CESSNOCK New South Wales 2325

1300 922 303 Int + 61 8 6201 3170 info@interfire.com.au www.interfire.com.au