

DATASHEET

LOOP 26 KN



GENERAL

Art.Nr:	L-0008-0,1
GTIN:	4030281063360
E-class number:	40-21-08-11
Customs tariff number:	63079098

Standards:	CEN/TS 16415:2013, EN 354:2010,EN 566: 2017,EN 795:2012/B
Net weight:	0.05 kg
Gross weight:	0.05 kg

DATASHEET

LOOP 26 KN

Belt sling with a load capacity of 26kN. Different lengths have different colours so that they can be easily distinguished. Is used in the rope access and rescue sector.

FEATURES

Colour:	Red
Fallindicator:	No
Hand wash:	40 °C
Edge approved:	No
Maximum lifetime:	10 years
Minimum tensile strength:	26.00 kN
Minimum temperature:	-35 °C
Maximum temperature:	45 °C

DIMENSIONS

length_lanyard:	0.10 m
-----------------	--------

MATERIAL

Material:	Polyamide
-----------	-----------

DATASHEET

LOOP 26 KN



GENERAL

Art.Nr:	L-0008-0,2
GTIN:	4030281051893
E-class number:	40-21-08-11
Customs tariff number:	63079098

Standards:	CEN/TS 16415:2013, EN 354:2010,EN 566: 2017,EN 795:2012/B
Net weight:	0.03 kg
Gross weight:	0.03 kg

DATASHEET

LOOP 26 KN

Belt sling with a load capacity of 26kN. Different lengths have different colours so that they can be easily distinguished. Is used in the rope access and rescue sector.

FEATURES

Colour:	Red
Fallindicator:	No
Hand wash:	40 °C
Edge approved:	No
Maximum lifetime:	10 years
Minimum tensile strength:	26.00 kN
Minimum temperature:	-35 °C
Maximum temperature:	45 °C

DIMENSIONS

length_lanyard:	0.20 m
-----------------	--------

MATERIAL

Material:	Polyamide
-----------	-----------

DATASHEET

LOOP 26 KN



GENERAL

Art.Nr:	L-0008-0,3
GTIN:	4030281063377
E-class number:	40-21-08-11
Customs tariff number:	63079098

Standards:	CEN/TS 16415:2013, EN 354:2010,EN 566: 2017,EN 795:2012/B
Net weight:	0.04 kg
Gross weight:	0.04 kg

DATASHEET

LOOP 26 KN

Belt sling with a load capacity of 26kN. Different lengths have different colours so that they can be easily distinguished. Is used in the rope access and rescue sector.

FEATURES

Colour:	Red
---------	-----

Fallindicator:	No
----------------	----

Hand wash:	40 °C
------------	-------

Edge approved:	No
----------------	----

Maximum lifetime:	10 years
-------------------	----------

Minimum tensile strength:	26.00 kN
---------------------------	----------

Minimum temperature:	-35 °C
----------------------	--------

Maximum temperature:	45 °C
----------------------	-------

DIMENSIONS

length_lanyard:	0.30 m
-----------------	--------

MATERIAL

Material:	Polyamide
-----------	-----------

DATASHEET

LOOP 26 KN



GENERAL

Art.Nr:	L-0008-0,4
GTIN:	4030281042310
E-class number:	40-21-08-11
Customs tariff number:	63079098

Standards:	CEN/TS 16415:2013, EN 354:2010,EN 566: 2017,EN 795:2012/B
Net weight:	0.05 kg
Gross weight:	0.05 kg

DATASHEET

LOOP 26 KN

Belt sling with a load capacity of 26kN. Different lengths have different colours so that they can be easily distinguished. Is used in the rope access and rescue sector.

FEATURES

Colour:	Red
Fallindicator:	No
Hand wash:	40 °C
Edge approved:	No
Maximum lifetime:	10 years
Minimum tensile strength:	26.00 kN
Minimum temperature:	-35 °C
Maximum temperature:	45 °C

DIMENSIONS

length_lanyard:	0.40 m
-----------------	--------

MATERIAL

Material:	Polyamide
-----------	-----------

DATASHEET

LOOP 26 KN



GENERAL

Art.Nr:	L-0008-0,6
GTIN:	4030281042327
E-class number:	40-21-08-11
Customs tariff number:	63079098

Standards:	CEN/TS 16415:2013, EN 354:2010,EN 566: 2017,EN 795:2012/B
Net weight:	0.06 kg
Gross weight:	0.06 kg

DATASHEET

LOOP 26 KN

Belt sling with a load capacity of 26kN. Different lengths have different colours so that they can be easily distinguished. Is used in the rope access and rescue sector.

FEATURES

Colour:	Red, Blue, Green
---------	------------------

Fallindicator:	No
----------------	----

Hand wash:	40 °C
------------	-------

Edge approved:	No
----------------	----

Maximum lifetime:	10 years
-------------------	----------

Minimum tensile strength:	26.00 kN
---------------------------	----------

Minimum temperature:	-35 °C
----------------------	--------

Maximum temperature:	45 °C
----------------------	-------

DIMENSIONS

length_lanyard:	0.60 m
-----------------	--------

MATERIAL

Material:	Polyamide
-----------	-----------

DATASHEET

LOOP 26 KN



GENERAL

Art.Nr:	L-0008-0,8
GTIN:	4030281042334
E-class number:	40-21-08-11
Customs tariff number:	63079098

Standards:	CEN/TS 16415:2013, EN 354:2010,EN 566: 2017,EN 795:2012/B
Net weight:	0.08 kg
Gross weight:	0.08 kg

DATASHEET

LOOP 26 KN

Belt sling with a load capacity of 26kN. Different lengths have different colours so that they can be easily distinguished. Is used in the rope access and rescue sector.

FEATURES

Colour:	Grey
Fallindicator:	No
Hand wash:	40 °C
Edge approved:	No
Maximum lifetime:	10 years
Minimum tensile strength:	26.00 kN
Minimum temperature:	-35 °C
Maximum temperature:	45 °C

DIMENSIONS

length_lanyard:	0.80 m
-----------------	--------

MATERIAL

Material:	Polyamide
-----------	-----------

DATASHEET

LOOP 26 KN



GENERAL

Art.Nr:	L-0008-1
GTIN:	4030281042341
E-class number:	40-21-08-11
Customs tariff number:	63079098

Standards:	CEN/TS 16415:2013, EN 354:2010,EN 566: 2017,EN 795:2012/B
Net weight:	0.10 kg
Gross weight:	0.10 kg

DATASHEET

LOOP 26 KN

Belt sling with a load capacity of 26kN. Different lengths have different colours so that they can be easily distinguished. Is used in the rope access and rescue sector.

FEATURES

Colour:	Grey
Fallindicator:	No
Hand wash:	40 °C
Edge approved:	No
Maximum lifetime:	10 years
Minimum tensile strength:	26.00 kN
Minimum temperature:	-35 °C
Maximum temperature:	45 °C

DIMENSIONS

length_lanyard:	1.00 m
-----------------	--------

MATERIAL

Material:	Polyamide
-----------	-----------

DATASHEET

LOOP 26 KN



GENERAL

Art.Nr:	L-0008-1,2
GTIN:	4030281042358
E-class number:	40-21-08-11
Customs tariff number:	63079098

Standards:	CEN/TS 16415:2013, EN 354:2010,EN 566: 2017,EN 795:2012/B
Net weight:	0.12 kg
Gross weight:	0.12 kg

DATASHEET

LOOP 26 KN

Belt sling with a load capacity of 26kN. Different lengths have different colours so that they can be easily distinguished. Is used in the rope access and rescue sector.

FEATURES

Colour:	Yellow
---------	--------

Fallindicator:	No
----------------	----

Hand wash:	40 °C
------------	-------

Edge approved:	No
----------------	----

Maximum lifetime:	10 years
-------------------	----------

Minimum tensile strength:	26.00 kN
---------------------------	----------

Minimum temperature:	-35 °C
----------------------	--------

Maximum temperature:	45 °C
----------------------	-------

DIMENSIONS

length_lanyard:	1.20 m
-----------------	--------

MATERIAL

Material:	Polyamide
-----------	-----------

DATASHEET

LOOP 26 KN



GENERAL

Art.Nr:	L-0008-1,5
GTIN:	4030281042365
E-class number:	40-21-08-11
Customs tariff number:	63079098

Standards:	CEN/TS 16415:2013, EN 354:2010,EN 566: 2017,EN 795:2012/B
Net weight:	0.14 kg
Gross weight:	0.14 kg

DATASHEET

LOOP 26 KN

Belt sling with a load capacity of 26kN. Different lengths have different colours so that they can be easily distinguished. Is used in the rope access and rescue sector.

FEATURES

Colour:	Yellow
Fallindicator:	No
Hand wash:	40 °C
Edge approved:	No
Maximum lifetime:	10 years
Minimum tensile strength:	26.00 kN
Minimum temperature:	-35 °C
Maximum temperature:	45 °C

DIMENSIONS

length_lanyard:	1.50 m
-----------------	--------

MATERIAL

Material:	Polyamide
-----------	-----------

DATASHEET

LOOP 26 KN



GENERAL

Art.Nr:	L-0008-1,8
GTIN:	4030281042433
E-class number:	40-21-08-11
Customs tariff number:	63079098

Standards:	CEN/TS 16415:2013, EN 354:2010,EN 566: 2017,EN 795:2012/B
Net weight:	0.17 kg
Gross weight:	0.17 kg

DATASHEET

LOOP 26 KN

Belt sling with a load capacity of 26kN. Different lengths have different colours so that they can be easily distinguished. Is used in the rope access and rescue sector.

FEATURES

Colour:	Blue
---------	------

Fallindicator:	No
----------------	----

Hand wash:	40 °C
------------	-------

Edge approved:	No
----------------	----

Maximum lifetime:	10 years
-------------------	----------

Minimum tensile strength:	26.00 kN
---------------------------	----------

Minimum temperature:	-35 °C
----------------------	--------

Maximum temperature:	45 °C
----------------------	-------

DIMENSIONS

length_lanyard:	1.80 m
-----------------	--------

MATERIAL

Material:	Polyamide
-----------	-----------

DATASHEET

LOOP 26 KN



GENERAL

Art.Nr:	L-0008-2
GTIN:	4030281042440
E-class number:	40-21-08-11
Customs tariff number:	63079098

Standards:	CEN/TS 16415:2013, EN 354:2010,EN 566: 2017,EN 795:2012/B
Net weight:	0.19 kg
Gross weight:	0.19 kg

DATASHEET

LOOP 26 KN

Belt sling with a load capacity of 26kN. Different lengths have different colours so that they can be easily distinguished. Is used in the rope access and rescue sector.

FEATURES

Colour:	Blue
Fallindicator:	No
Hand wash:	40 °C
Edge approved:	No
Maximum lifetime:	10 years
Minimum tensile strength:	26.00 kN
Minimum temperature:	-35 °C
Maximum temperature:	45 °C

DIMENSIONS

length_lanyard:	2.00 m
-----------------	--------

MATERIAL

Material:	Polyamide
-----------	-----------

DATASHEET

LOOP 26 KN



GENERAL

Art.Nr:	L-0008-3,4	Standards:	CEN/TS 16415:2013, EN 354:2010,EN 566: 2017,EN 795:2012/B
GTIN:	4030281088325	Net weight:	0.34 kg
E-class number:	40-21-08-11	Gross weight:	0.34 kg
Customs tariff number:	63079098		

DATASHEET

LOOP 26 KN

Belt sling with a load capacity of 26kN. Different lengths have different colours so that they can be easily distinguished. Is used in the rope access and rescue sector.

FEATURES

Colour:	Blue
Fallindicator:	No
Hand wash:	40 °C
Edge approved:	No
Maximum lifetime:	10 years
Minimum tensile strength:	26.00 kN
Minimum temperature:	-35 °C
Maximum temperature:	45 °C

DIMENSIONS

length_lanyard:	3.40 m
-----------------	--------

MATERIAL

Material:	Polyamide
-----------	-----------

DATASHEET

LOOP 26 KN



GENERAL

Art.Nr:	L-0008-4
GTIN:	4030281077183
E-class number:	40-21-08-11
Customs tariff number:	63079098

Standards:	CEN/TS 16415:2013, EN 354:2010,EN 566: 2017,EN 795:2012/B
Net weight:	0.37 kg
Gross weight:	0.37 kg

DATASHEET

LOOP 26 KN

Belt sling with a load capacity of 26kN. Different lengths have different colours so that they can be easily distinguished. Is used in the rope access and rescue sector.

FEATURES

Colour:	Blue
Fallindicator:	No
Hand wash:	40 °C
Edge approved:	No
Maximum lifetime:	10 years
Minimum tensile strength:	26.00 kN
Minimum temperature:	-35 °C
Maximum temperature:	45 °C

DIMENSIONS

length_lanyard:	4.00 m
-----------------	--------

MATERIAL

Material:	Polyamide
-----------	-----------