

# DATASHEET

## RAPTOR C20 HUB J



### GENERAL

Art.Nr:	HSG-044-20-J	Standards:	EN 1496-A:2017, EN 360:2002
GTIN:	4030281023357	Net weight:	14.86 kg
E-class number:	40-02-01-03	Gross weight:	14.86 kg
Customs tariff number:	84798997		

## DATASHEET

### RAPTOR C20 HUB J

The RAPTOR HUB fall arrester with a 20 m steel cable and automatic blocking function enables safe working at heights and depths. Unlike the RAPTOR, the RAPTOR HUB is also equipped with a rescue lifting device that can be activated in an emergency and enables a quick rescue. After verification by a skilled person is able to use the device again after using the rescue lifting device, which increases its cost-effectiveness.

RAPTOR HUB offers maximum application possibilities, as it can be used both independently at anchor points in accordance with EN795 and in combination with the individual bracket ACS-0164-JP for the JACKPOD TRI. The holder can remain attached to the mobile attachment point when the device is removed.

RAPTOR HUB has a modular design so that components can be replaced, which increases the longevity of the devices and reduces maintenance costs. The retractable type fall arrester has two visible fall indicators that show the product's functionality from the outside. A red indicator signals to the user as soon as the device needs to be checked. The well thought-out housing design also enables space-saving and device-friendly storage.

The device is certified according to EN 360:2002, EN 1496:2017/A and secures a person with a maximum user weight of 140 kg.

#### FEATURES

Colour:	Black
Edge approved:	No
Maximum lifetime:	20 years
Maximum number of persons:	1
Minimum user weight:	40.00 kg
Maximum user weight vertical:	140.00 kg
Minimum temperature:	-35 °C
Maximum temperature:	45 °C

#### DIMENSIONS

Rope length:	20.00 m
--------------	---------

#### MATERIAL

Material:	Various
-----------	---------