

DATASHEET

UP YOU GO



GENERAL

Art.Nr:	H-250
GTIN:	8057733308912
E-class number:	40-21-90-90
Customs tariff number:	84251900

Net weight:	0.64 kg
Gross weight:	0.64 kg

DATASHEET

UP YOU GO

Self-locking retractable pulley block, with reduction factor 4, or 5 if used the other way round. Ideal for use during rescue operations. Designed to enable the lifting and lowering of an injured user or to tension a device

Main features:

- CE-marked and tested with a load of 18 kN for 3 minutes;
- Extremely compact system that can also be used where space is limited;
- Prevents the load from retracting after being hauled in, making the operation quick and easy;
- Consists of the UP ROLL and UP LOCK pulleys, with pulleys running on ball bearings;
- Equipped with a resealable pouch that enables minimal packing size for transportation;
- opening with drawstring for quick readiness when pulling out the device guaranteed;
- Equipped with a rope guide (patent pending) positioned on the lower pulley, which keeps the ropes parallel and reduces the risk of twisting during use;
- Possibility to unlock or lock the cam thanks to the Freelock system, which can be activated with a single hand movement even when wearing gloves;
- Equipped with two OVX TG oval carabiners with triplex screw link and anti-rotation systems;
- Equipped with 8 mm lanyard EN 564.

FEATURES

Application areas:

Various, Arborists, Bouldering, Emergency, Facades cleaning, Work on roofs and facades, High Rack storage, High ropes courses, Tactical approach, Off Shore Industry, Rope access, Rescue, Roofers, Route construction, Scaffolding, Shaft, Working on masts and towers, Wind energy, Working in confined spaces

Colour:

Various

DIMENSIONS

Rope length:

1.00 m

MATERIAL

Material:

Various

DATASHEET

UP YOU GO



GENERAL

Art.Nr:	H-251
GTIN:	8057733308929
E-class number:	40-21-90-90
Customs tariff number:	84251900

Net weight:	0.85 kg
Gross weight:	0.85 kg

DATASHEET

UP YOU GO

Self-locking retractable pulley block, with reduction factor 4, or 5 if used the other way round. Ideal for use during rescue operations. Designed to enable the lifting and lowering of an injured user or to tension a device

Main features:

- CE-marked and tested with a load of 18 kN for 3 minutes;
- Extremely compact system that can also be used where space is limited;
- Prevents the load from retracting after being hauled in, making the operation quick and easy;
- Consists of the UP ROLL and UP LOCK pulleys, with pulleys running on ball bearings;
- Equipped with a resealable pouch that enables minimal packing size for transportation;
- opening with drawstring for quick readiness when pulling out the device guaranteed;
- Equipped with a rope guide (patent pending) positioned on the lower pulley, which keeps the ropes parallel and reduces the risk of twisting during use;
- Possibility to unlock or lock the cam thanks to the Freelock system, which can be activated with a single hand movement even when wearing gloves;
- Equipped with two OVX TG oval carabiners with triplex screw link and anti-rotation systems;
- Equipped with 8 mm lanyard EN 564.

FEATURES

Application areas:	Various, Arborists, Elevator construction, Emergency, Facades cleaning, Work on roofs and facades, High Rack storage, High ropes courses, Tactical approach, Off Shore Industry, Rope access, Rescue, Roofers, Route construction, Scaffolding, Shaft, Working on masts and towers, Wind energy, Working in confined spaces
--------------------	---

Colour:	Various
---------	---------

DIMENSIONS

Rope length:	2.00 m
--------------	--------

MATERIAL

Material:	Various
-----------	---------

DATASHEET

UP YOU GO



GENERAL

Art.Nr:	H-252
GTIN:	8057733308936
E-class number:	40-21-90-90
Customs tariff number:	84251900

Net weight:	1.50 kg
Gross weight:	1.50 kg

DATASHEET

UP YOU GO

Self-locking retractable pulley block, with reduction factor 4, or 5 if used the other way round. Ideal for use during rescue operations. Designed to enable the lifting and lowering of an injured user or to tension a device

Main features:

- CE-marked and tested with a load of 18 kN for 3 minutes;
- Extremely compact system that can also be used where space is limited;
- Prevents the load from retracting after being hauled in, making the operation quick and easy;
- Consists of the UP ROLL and UP LOCK pulleys, with pulleys running on ball bearings;
- Equipped with a resealable pouch that enables minimal packing size for transportation;
- opening with drawstring for quick readiness when pulling out the device guaranteed;
- Equipped with a rope guide (patent pending) positioned on the lower pulley, which keeps the ropes parallel and reduces the risk of twisting during use;
- Possibility to unlock or lock the cam thanks to the Freelock system, which can be activated with a single hand movement even when wearing gloves;
- Equipped with two OVX TG oval carabiners with triplex screw link and anti-rotation systems;
- Equipped with 8 mm lanyard EN 564.

FEATURES

Application areas:

Various, Arborists, Elevator construction, Emergency, Facades cleaning, Work on roofs and facades, High Rack storage, High ropes courses, Tactical approach, Off Shore Industry, Rope access, Rescue, Roofers, Route construction, Scaffolding, Shaft, Working on masts and towers, Wind energy, Working in confined spaces

Colour:

Various

DIMENSIONS

Rope length:

5.00 m

MATERIAL

Material:

Various