

DATASHEET

TUNER PRO FLEX



GENERAL

Art.Nr:	L-1019
GTIN:	8053841303054
E-class number:	40-21-08-13
Customs tariff number:	56090000000001

Net weight:	0.39 kg
Gross weight:	0.47 kg

www.skylotec.com | Datenblatt, 26.03.25

AVAILABLE FROM



National Sales Office & Warehouse
Unit 1 / 23 Christable Way
LANDSDALE Western Australia 6055
1300 922 303
+ 61 8 6201 3170
interfire.com.au
info@interfire.com.au

South Australian Office &
Warehouse Unit 9 / 28 Heath St
LONSDALE South Australia, 5160
1300 922 303
+ 61 8 6201 3170
interfire.com.au
info@interfire.com.au

DATASHEET

TUNER PRO FLEX

Multipurpose lanyard developed for rope access, work at height and rescue. Equipped with a double adjuster and seamless rope for a more versatile connection to the harness.

Main features:

- it offers the highest working loads on the market despite its compact size and low weight;
- the adjuster stands out for its mobile system (Patent Pending) that guarantees immediate and safe locking of the rope regardless of the shape of the Used EN 362 connector;
- the special geometry of the adjusters allows the length of the lanyard to be managed smoothly and precisely;
- the lanyard can be released intuitively, with just one hand even with a light load, by holding the adjuster and pressing the release button;
- equipped with a 9.6 mm EN 1891-A rope, light, flexible and designed for the most intense uses;
- it can be connected directly to the harness using a figure of eight knot;
- configurable as a cow's tail for rope access or for moving stretchers (uses not covered by the certification);
- equipped with elastic terminal loops that allow the free sides of the rope to be positioned during use;
- CE compliant, it is tested according to some points of the EN 358.

FEATURES

Colour: Black, Orange

Maximum lifetime: 12 years

Minimum temperature: -30 °C

Maximum temperature: 50 °C

Patent status: Patent pending

Individually tested: No

100% quality control: Yes

DIMENSIONS

length_lanyard: 3.60 m

Lanyard rope diameter: 9.60 mm

MATERIAL

Material: Aluminium, Polyamide

www.skylotec.com | Datenblatt, 26.03.25

AVAILABLE FROM



National Sales Office & Warehouse
Unit 1 / 23 Christable Way
LANDSDALE Western Australia 6055
1300 922 303
+ 61 8 6201 3170
interfire.com.au
info@interfire.com.au

South Australian Office &
Warehouse Unit 9 / 28 Heath St
LONSDALE South Australia, 5160
1300 922 303
+ 61 8 6201 3170
interfire.com.au
info@interfire.com.au