

RECHARGEABLE

INTRANT™ DUAL-LIGHT ANGLE LIGHT

NIGHTSTICK®
Life Depends on Light™



HEAD ROTATES 90°

45°

EXCLUSIVE
DOWNWARD FLOODLIGHT




ALSO AVAILABLE IN SAFETY RED.




Head rotates 90° – directing beam exactly where it's needed most



45° downward floodlight lights an 8 foot walking area



Easy-to-use with gloves, the large switches **independently control** separate LEDs



Heavy-duty, clip and V-ring securely holds **tight to gear** in any situation

GRAB-N-GO
CHARGING BASE



AVAILABLE FROM

National Sales Office & Warehouse
Unit 1 / 23 Christable Way
LANDSDALE Western Australia 6055
1300 922 303
+ 61 8 6201 3170
interfire.com.au
info@interfire.com.au

South Australian Office &
Warehouse Unit 9 / 28 Heath St
LONSDALE South Australia, 5160
1300 922 303
+ 61 8 6201 3170
interfire.com.au
info@interfire.com.au

205 LUMENS



DUAL-LIGHT ANGLE LIGHT

RECHARGEABLE

ITEM NUMBER/UPC

XPR-5568RX (Red), 0 17398 80631 2
XPR-5568RXLB (Red, Light & Battery Only), 0 17398 80697 8
XPR-5568GX (Green), 0 17398 80630 5

CERTIFICATIONS

- CE, cULus, ATEX, IECEx, InMetro, UKCA, KOSHA
- Meets requirements of NFPA

PATENTS

- 9,713,217 10,119,663

CASE MATERIAL

- Engineered polymer

LUMENS/RUNTIME

FLASHLIGHT

- HIGH: 200L, 7 hrs. runtime
- MEDIUM: 110L, 15 hrs. runtime
- LOW: 60L, 27 hrs. runtime
- STROBE

FLOODLIGHT

- HIGH: 100L, 7 hrs. runtime
- MEDIUM: 40L, 15 hrs. runtime
- SURVIVAL: 20L, 27 hrs. runtime

DUAL-LIGHT

- 205L, 7 hrs. runtime

CANDELA

FLASHLIGHT

- HIGH: 40,256
- MEDIUM: 15,625
- LOW: 8,750

BEAM DISTANCE

FLASHLIGHT

- HIGH: 401m
- MEDIUM: 250m
- LOW: 187m

WATER RATING

- IP-67 (dustproof and waterproof)

DROP RATING

- 2 meters

DIMENSIONS

- LENGTH: 6.6 in (168mm)
- WIDTH: 2.6 in (66mm)
- DEPTH: 2.6 in (66mm)
- HEAD DIAMETER: 2.1 in (53mm)
- WEIGHT: 10.6 oz (301g)(with batteries)

FL 1 STANDARD	SPOT HIGH	SPOT LOW	DUAL-LIGHT
	200 LUMENS	60 LUMENS	205 LUMENS
	7h	27h	7h
	401m		
	40256cd		

Bayco Product, Inc. XPR-5568
640 S. Sanden Blvd., Wylie, TX 75098

Ex in FLASHLIGHT FOR USE IN HAZARDOUS LOCATIONS LISTED Ex in PARAUSO EM LOCAB PERICOLOS
Para uso con a bateria de lonas de Bayco 5568-BATT ou 5568-CARRIER with 3 AA Energizer Type EN91 ou E91 batteries only
E 457755 ID 400354

CLASS I DIV 1 GRP B A-D T4 CLASS II & III DIV 1 GRP B E-G T130°C © I 1 M Ex in op in I Ma Ex in op in I Ma
CLASS I ZONE 0 AEx in IC T4 Ga CLASS I G Ex in op in IC T4 Ga Ex in op in IC T4 Ga

US Patents 9,713,217 & 10,119,663

CE 2575 **UK CA 0359** **IECEx** **NFPA** **UK CA 0359** **INMETRO** **BC** **8** **ICs**

Meets the requirements of NFPA-1971-8.6 (2013)

DEMCO 11 ATEX 1527 UL2000C000 IECEx UL 17.0082 20°C ≤ Tamb ≤ +40°C 3.7VDC Recharge 3.7VDC Li-ion IP-67 Um: 10V SEE INSTRUCTION MANUAL VORH MANUEL MFG MM-YY

Control Drawing: 5568-CERT-DWG1-03
For Battery Charger Connection see Instruction Manual Drawing: 5562-68-MECH-DWG1-09



BATTERY

- Rechargeable Li-ion battery pack
- AA Battery carrier (batteries not included)

WARRANTY

- Limited lifetime warranty

WHAT'S INCLUDED

- Angle light
- Rechargeable Li-ion battery pack
- AA battery carrier
- Snap-in rapid charger (Charge Input: 24VDC max) Meets requirements of NFPA
- AC & DC power supplies
- Instruction manual

AVAILABLE FROM



National Sales Office & Warehouse
Unit 1 / 23 Christable Way
LANDSDALE Western Australia 6055
1300 922 303
+ 61 8 6201 3170
interfire.com.au
info@interfire.com.au

South Australian Office &
Warehouse Unit 9 / 28 Heath St
LONSDALE South Australia, 5160
1300 922 303
+ 61 8 6201 3170
interfire.com.au
info@interfire.com.au