

LI-ION RECHARGEABLE

XPR-5584GMX

INTEGRITAS™ INTRINSICALLY SAFE LANTERN

**NIGHTSTICK**  
Life Depends on Light™

**600**

**POWERFUL  
LUMENS**

INCLUDING HIGH & LOW

**NIGHTSTICK**  
INTEGRITAS 84


180° DOWNWARD ROTATION

**ATEX  
ZONE 0  
IECEx**

**CLASS I  
DIV 1**



**Rear green safety lights**  
provide visibility in smoke filled applications



**Powerful rare-earth tail magnets**  
for additional hands-free use



**Convenient locking snap-in  
charger included**



Dustproof/Waterproof (IP-67) and  
chemical/heat resistant for any  
environment



AVAILABLE FROM

**600 LUMENS**

  
**InterFire**  
— AGENCIES —

National Sales Office & Warehouse  
Unit 1 / 23 Christable Way  
LANDSDALE Western Australia 6055  
1300 922 303  
+ 61 8 6201 3170  
interfire.com.au  
info@interfire.com.au

South Australian Office &  
Warehouse Unit 9 / 28 Heath St  
LONSDALE South Australia, 5160  
1300 922 303  
+ 61 8 6201 3170  
interfire.com.au  
info@interfire.com.au

**INTEGRITAS™**

# LANTERN

**LI-ION RECHARGEABLE****ITEM NUMBER/UPC**

XPR-5584GMX UPC# 0 17398807586

**MARKET APPLICATIONS**

Hazardous work environments, fire, rescue, industrial and automotive

**CERTIFICATIONS**

- ATEX, IECEx, InMetro, CE, cULus, UKCA, KOSHA
- Charger meets requirements of NFPA-1901 (2009) Mounted in any Position

**CASE MATERIAL**

- Glass filled nylon polymer

**LUMENS/RUNTIME****FLASHLIGHT**

- HIGH: 600L, 13 hrs. runtime
- LOW: 250L, 25 hrs. runtime

**CANDELA****FLASHLIGHT**

- HIGH: 14,096
- LOW: 7,007

**BEAM DISTANCE****FLASHLIGHT**

- HIGH: 237m
- LOW: 167m

**WATER RATING**

- IP-67 (dustproof and waterproof)

**DROP RATING**

- 2 meters

**DIMENSIONS**

- LENGTH: 7.54 in / 19.2 cm
- WIDTH: 4.26 in / 10.8 cm
- DEPTH: 5.83 in / 14.8 cm
- WEIGHT: 2 lbs. 11 oz. / 1219 g

**BATTERY**

- Rechargeable Li-ion integrated battery pack

**WARRANTY**

- Limited lifetime warranty

**PATENTED**

- US PATENTS 9,713,217 & 10,879,519

**WHAT'S INCLUDED**

- Lantern w/ Integrated 5582-MAGNET Pad (preinstalled)
- Standard Rubber Pad
- Li-ion rechargeable battery pack
- Locking snap-in charger (5582-CHGR2)
- AC Charging Cord
- DC Charging Cord
- Removable shoulder strap (5580-STRAP)
- Instruction manual

FL 1 STANDARD	HIGH	LOW
	<b>600 LUMENS</b>	<b>250 LUMENS</b>
	<b>13h</b>	<b>25h</b>
	<b>237m</b>	<b>167m</b>
	<b>14096cd</b>	<b>7007cd</b>

**Bayco Products, Inc. XPR-5584GMX**  
640 S. Sanden Blvd., Wylie, TX 75098

Ex in FLASHLIGHT FOR USE IN HAZARDOUS LOCATIONS  
UL listed for use with Bayco Li-ion Battery Pack 5584-BATT

CLASS I DIV 1 GRPS A-D T4  
CLASS II & III DIV 1 GRPS E-G T135°C  
CLASS I ZONE 0 AEx in op is IIC T4 Gc  
Ex in op is IIC T4 Gc  
CLASS II ZONE 0 AEx in op is IIC T4 Gc  
Ex in op is IIC T4 Gc  
CLASS II ZONE 0 AEx in op is IIC T4 Gc  
Ex in op is IIC T4 Gc

DEMKO 19 ATEX 2254  
ULZUNEX 2268  
IECEx UK 19 0075  
20°C ≤ Tamb ≤ +40°C  
3.7V/Cell 5584-BATT  
Um 10V

WARNING: Do not charge battery in a hazardous location  
WARNING: Do not replace battery when an explosive atmosphere is present

ATENÇÃO - UTILIZAR SOMENTE BATERIAS 5584-BATT.  
ATENÇÃO - NÃO SUBSTITUIR A BATERIA QUANDO UMA ATMOSFERA EXPLOSIVA  
PUDESSER PRESENTE.  
ATENÇÃO - NÃO RECARREGUE A BATERIA EM ÁREAS CLASSIFICADAS.

SEE INSTRUCTION MANUAL  
VOIR MANUEL

MFG MM-YY



AVAILABLE FROM



National Sales Office & Warehouse  
Unit 1 / 23 Christable Way  
LANDSDALE Western Australia 6055  
1300 922 303  
+ 61 8 6201 3170  
interfire.com.au  
info@interfire.com.au

South Australian Office &  
Warehouse Unit 9 / 28 Heath St  
LONSDALE South Australia, 5160  
1300 922 303  
+ 61 8 6201 3170  
interfire.com.au  
info@interfire.com.au