# PAB FIRE 05

**GLASS FIBRE REINFORCED THERMOPLASTIC** 



AVAILABLE FROM



National Sales Office & Warehouse Unit 1/23 Christable Way LANDSDALE Western Australia 6055 1300 922 303 + 61 8 6201 3170

South Australian Office & Warehouse Unit 9 / 28 Heath St LONSDALE South Australia, 5160 1300 922 303

+ 61 8 6201 3170 interfire.com.au info@interfire.com.au New, modern design and excellent protection properties. Optimal relationship between protection and comfort with a broad spectrum of optional upgrades. Structural firefighting has never been safer.

# PERFORMANCE

- Extreme temperature resistance (up to 1,000°C in a 10 second flash over flames)
- Long-term temperature resistance (radiant heat test 14 kW/m²)
- High resistance to mechanical impacts
- Low-temperature classification -30°C

# SAFETY

- Electrical insulation capacity E2 and E3
- Full head protection (including neck and face)
- Interior shock absorber
- Reflective elements for better visibility in low-light conditions
- Neck protector (available in aluminised fibre, Nomex, genuine leather or wool for Holland style)
- 3 point chinstrap (tested to prevent skin irritation, fire retardant aramid tape)
- Chemical resistance (according to EN 443)
- Type B3b

# **©**OMFORT

- Lightweight
- Integrated adjustment system
- One shell size for head sizes from 52 to 66 cm Wide range of accessories and high level of personalisation

# WEIGHT

- 1445 g ± 30 g (basic configuration without accessories)
- 1515 g ± 30 g (basic configuration with aluminised neck protector)

## HIGH TECH MATERIALS

- Flame retardant and high temperature resistant composite
- Anti-scratch and anti-fog coated integrated visor (EN 14458:2004)
- Anti-scratch and anti-fog coated integrated goggle (EN 166 and EN 14458)









### CERTIFICATES

EN 443:2008 | EN 14458:2004 | EN 166:2004 | @ MED Approved





















